

	Type	L #	Hits	Search Text	DBs	Time Stamp	Comments	Error Definition
1	BRS	L1	932	high with low with (seals or seal or sealing or sealings) with piston	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	2005/06/12 22:37		
2	BRS	L2	755	1 with pressure	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	2005/06/12 22:37		
3	BRS	L3	1	2 and (lubricator)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	2005/06/12 22:37		
4	BRS	L4	177	high with low with (seals or sealings) with piston	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	2005/06/12 22:37		
5	BRS	L5	143	4 with pressure	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	2005/06/12 22:38		
6	BRS	L6	0	5 and (lubricant with injector)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	2005/06/12 22:38		
7	BRS	L7	12	5 and (lubricant)	US-PGPUB; USPAT; EPO; JPO; DERWENT; IBM_TDB	2005/06/12 22:38		